

REACT

QUALITY FIRST

FORKLIFTS



REACT ALL-TERRAIN FORKLIFTS X/Y MODELS 2.0T, 2.5T, 3.0T, 3.5T

FEATURES

- Optional YANMAR 65hp Diesel Engines
- 4.5m 3 Stage Container Mast
- Automatic Transmission
- Optional Mast Sizes
 - Container Mast
 - 2 Stage Mast 3.0m / 3.5m / 4.0m
 - 3 Stage Mast 4.5m / 5.0m / 5.5m / 6.0m
- Fork Positioner
- Side Shifter
- Optional Fork Tyne Lengths
- Pneumatic Tire
- Top-Grade Seat
- LED Lights
- Reverse Alarm
- Large Aluminium Radiator

RIV1220

IAN EVANS
0427 180 673
IAN@TOUGHINDUSTRIAL.COM.AU

SHANE BLUMSON
0436 521 151
SHANE@TOUGHINDUSTRIAL.COM.AU

LOCATION: 15 CARDIFF CRT. CAVAN. ADELAIDE - SOUTH AUSTRALIA

REACT

QUALITY FIRST

REACT ALL-TERRAIN FORKLIFTS

		Model	Y/X 2.0T	Y/X 2.5T	Y/X 3.0T	Y/X 3.5T
GENERAL	1	Rated Capacity	2,000kg	2,500kg	3,000kg	3,500kg
	2	Load Center	500mm	500mm	500mm	500mm
	3	Power Type	Diesel	Diesel	Diesel	Diesel
	4	Transmission	Automatic	Automatic	Automatic	Automatic
DIMENSIONS	5	Lifting Height	4,500mm	4,500mm	4,500mm	4,500mm
	6	Free Lifting Height	1,540mm	1,540mm	1,540mm	1,540mm
	7	Turning Radius	2,950mm	2,950mm	3,000mm	3,000mm
	8	Overall Length	4,010mm	4,010mm	4,260mm	4,260mm
	9	Overall Width	1,568mm	1,568mm	1,620mm	1,620mm
	10	Overall Height (Mast Lowered)	2,280mm	2,280mm	2,320mm	2,320mm
	11		2,280mm	2,280mm	2,320mm	2,320mm
	12	Overall Height (Mast Raised)	5,565mm	5,565mm	5,770mm	5,770mm
	13	Overall Height (Overhead Guard)	2,270mm	2,270mm	2,315mm	2,315mm
	15	Fork Length	1,070mm	1,070mm	1,220mm	1,220mm
	16	Fork Width	122mm	122mm	122mm	122mm
	17	Fork Thickness	40mm	40mm	45mm	45mm
	PERFORMANCE	18	Max. Driving Speed (With/Without Load)	19.5/21km/h	19.5/21km/h	21/23km/h
19		Max. Lifting Speed (With Load)	570mm/s	570mm/s	440mm/s	440mm/s
20		Departure Angle	32 °	32 °	30 °	30 °
21		Min. Ground Clearance	290mm	290mm	320mm	320mm
22		Tilting Angles (Forward/Backward)	6/6 °	6/6 °	6/6 °	6/6 °
23		Service Weight	4,150kg	4,400kg	4,900kg	5,150kg
ENGINE	24	Engine Model	Xinchai 495BPG	Xinchai 495BPG	Xinchai 4D35G	Xinchai 4D35G
	25	Power	42kW / 57hp	42kW / 57hp	48kW / 65.3hp	48kW / 65.3hp
	26	Rated Speed	2,650rpm	2,650rpm	2,450rpm	2,450rpm
	27	Displacement	2.97L	2.97L	3.168L	3.168L
	28	No. Of Cylinder	4	4	4	4
WHEEL	29	Front Overhang	550mm	550mm	590mm	590mm
	30	Wheel Base	1,800mm	1,800mm	1,850mm	1,850mm
	31	Front Tread	1,240mm	1,240mm	1,250mm	1,250mm
	32	Rear Tread	1,175mm	1,175mm	1,175mm	1,175mm
	33	Front Tire	12-16.5-14	12-16.5-14	14-17.5-14	14-17.5-14
	34	Rear Tire	27*10-12	27*10-12	27*10-12	27*10-12

***(Y)** Yanmar or **(X)** Xinchai
diesel engine options