

REACT

QUALITY FIRST



REACT DIESEL FORKLIFTS

2.0T, 2.5T, 3.0T, 3.5T, 4.0T, 4.5T, 5.0T, 7.0T, 10.0T

FEATURES

- Optional Japanese Diesel Engines
- Optional Chinese Diesel Engines
- Automatic Transmission
- Optional Mast Sizes
 - Container Mast
 - 2 Stage Mast 3.0m / 3.5m / 4.0m
 - 3 Stage Mast 4.5m / 5.0m / 5.5m / 6.0m
- Fork Postioner
- Side Shift
- Optional Fork Tyne Lengths
- Pneumatic Tire
- Top-Grade Seat
- LED Lights
- Reverse Alarm
- Large Aluminum Radiator
- Duel Drive Wheel Option Available

FORKLIFTS

RIV1220

IAN EVANS
0427 180 673
IAN@TOUGHINDUSTRIAL.COM.AU

SHANE BLUMSON
0436 521 151
SHANE@TOUGHINDUSTRIAL.COM.AU

LOCATION: 15 CARDIFF CRT. CAVAN. ADELAIDE - SOUTH AUSTRALIA

REACT

QUALITY FIRST

REACT DIESEL FORKLIFTS

		Model	XD2.0T	XD2.5T	XD3.0T
GENERAL	1	Rated Capacity	2,000kg	2,500kg	3,000kg
	2	Load Center	500mm	500mm	500mm
	3	Power Type	Diesel / LPG	Diesel / LPG	Diesel / LPG
	4	Transmission	Automatic	Automatic	Automatic
DIMENSIONS	5	Lifting Height	3 stage 4.5m	3 stage 4.5m	3 stage 4.5m
	6	Free Lifting Height	1150mm	1150mm	1150mm
	7	Turning Radius	2170mm	2240mm	2445mm
	8	Overall Length	2530mm	2530mm	2705mm
	9	Overall Width	1,150mm	1,150mm	1,225mm
	10	Overall Height (Mast Lowered)	2,100mm	2,100mm	2,100mm
	11	Overall Height (Mast Raised)	5,500mm	5,500mm	5,500mm
	12	Overall Height (Overhead Guard)	2,100mm	2,100mm	2,140mm
	13	Fork Length	1,070mm	1,070mm	1,070mm
	14	Fork Width	122mm	122mm	125mm
	15	Fork Thickness	40mm	40mm	45mm
PERFORMANCE	16	Max. Driving Speed (With/Without Load)	17/19km/h	17/19km/h	18/20km/h
	17	Max. Lifting Speed (With Load)	580mm/s	580mm/s	500mm/s
	18	Max. Traction (With/Without)Load)	550mm/s	550mm/s	450mm/s
	19	Gradeability (With/Without Load)	15/20%	15/20%	15/20%
	20	Tilting Angles (Forward/Backward)	6/12 °	6/12 °	6/12 °
	21	Service Weight	3,320kg	3,600kg	4,380kg
ENGINE	22	Engine Model	490BPG	490BPG	490BPG
	23	Power	39kW	39kW	39kW
	24	Rated Speed	2,650rpm	2,650rpm	2,650rpm
	25	Displacement	2.67L	2.67L	2.67L
	26	No. Of Cylinder	4	4	4
WHEEL	27	Front Overhang	110mm	110mm	120mm
	28	Wheel Base	1,600mm	1,600mm	1,700mm
	29	Front Tread	970mm	970mm	1,000mm
	30	Rear Tread	970mm	970mm	970mm
	31	Front Tire	7.00-12	7.00-12	28x9-15 12pl
	32	Rear Tire	6.00-9	6.00-9	7.00-12

REACT DIESEL FORKLIFTS

		Model	XD3.5T	XD4.0T	XD4.5T
GENERAL	1	Rated Capacity	3,500kg	4,000kg	4,500kg
	2	Load Center	500mm	500mm	500mm
	3	Power Type	Diesel	Diesel	Diesel
	4	Transmission	Automatic	Automatic	Automatic
DIMENSIONS	5	Lifting Height	4.5m 3 stage	4.5m 3 stage	4.5m 3 stage
	6	Free Lifting Height	1,150mm	1,150mm	1,150mm
	7	Turning Radius	2,495mm	2,530mm	2,860mm
	8	Overall Length	2,760mm	2870mm	3,183mm
	9	Overall Width	1,285mm	1365mm	1,485mm
	10	Overall Height (Mast Lowered)	2,100mm	2,150mm	2,300mm
	11	Overall Height (Mast Raised)	5,500mm	5,500mm	5,600mm
	12	Overall Height (Overhead Guard)	2,140mm	2,140mm	2,270mm
	13	Fork Length	1,220mm	1,220mm	1,220mm
	14	Fork Width	125mm	150mm	150mm
	15	Fork Thickness	50mm	50mm	50mm
PERFORMANCE	16	Max. Driving Speed (With/Without Load)	17/19km/h	18/20km/h	20km/h
	17	Max. Lifting Speed (With Load)	500mm/s	480mm/s	430mm/s
	18	Max. Traction (With/Without)Load)	16/11kN	16.5/11.5kN	31/18kN
	19	Gradeability (With/Without Load)	15/20%	15/20%	15/20%
	20	Tilting Angles (Forward/Backward)	6/12 °	6/12 °	6/12 °
	21	Service Weight	4,780kg	5,050kg	6,800kg
ENGINE	22	Engine Model	A498BT1	A498BT1	Optional
	23	Power	42kW	42kW	60kW
	24	Rated Speed	2,400rpm	2,400rpm	2,400/2,200rpm
	25	Displacement	2.67L	2.67L	4.6L
	26	No. Of Cylinder	4	4	4
	27	Front Overhang	480mm	480mm	560mm
WHEEL	28	Wheel Base	1,700mm	1,800mm	2,000mm
	29	Front Tread	1,000mm	1,000mm	1,180mm
	30	Rear Tread	970mm	970mm	1,190mm
	31	Front Tire	28x9-15/12ply	28x9-15/12ply	300-15/18ply
	32	Rear Tire	6.50-10/10ply	6.50-10/10ply	7.00-12/12ply



QUALITY FIRST

REACT DIESEL FORKLIFTS

FORKLIFTS

		Model	XD5.0T	XD7.0T	XD10.0T
GENERAL	1	Rated Capacity	5,000kg	7,000kg	10,000kg
	2	Load Center	600mm	600mm	600mm
	3	Power Type	Diesel	Diesel	Diesel
	4	Transmission	Automatic	Automatic	Automatic
DIMENSIONS	5	Lifting Height	4.5m, 3 stage	4.5m, 3 stage	4.5m, 3 stage
	6	Free Lifting Height	1,500mm	1,500mm	1,500mm
	7	Turning Radius	3,250mm	3,360mm	3,900mm
	8	Overall Length	3,455mm	3,590mm	4,255mm
	9	Overall Width	1,995mm	1,995mm	2,245mm
	10	Overall Height (Mast Lowered)	2,500mm	2,500mm	2,850mm
	11	Overall Height (Mast Raised)	5,500mm	5,600mm	5,600mm
	12	Overall Height (Overhead Guard)	2,450mm	2,450mm	2,560mm
	13	Fork Length	1,220mm	1,220mm	1,220mm
	14	Fork Width	150mm	150mm	175mm
	15	Fork Thickness	60mm	65mm	80mm
PERFORMANCE	16	Max. Driving Speed (With/Without Load)	22/26km/h	22/26km/h	16/24km/h
	17	Max. Lifting Speed (With Load)	550mm/s	550mm/s	410mm/s
	18	Max. Traction (With/Without)Load)	54kN	52kN	57kN
	19	Gradeability (With/Without Load)	20/27%	20/25%	19/20%
	20	Tilting Angles (Forward/Backward)	6/12 °	6/12 °	6/12 °
	21	Service Weight	8,050kg	9,500kg	12,510kg
ENGINE	22	Engine Model	Optional	Optional	Optional
	23	Power	60kW	75kW	85kW
	24	Rated Speed	2,300rpm	2,300rpm	2,300rpm
	25	Displacement	4.99L	5.61L	6.49L
	26	No. Of Cylinder	6	6	6
WHEEL	27	Front Overhang	630mm	630mm	718mm
	28	Wheel Base	2,250mm	2,250mm	2,800mm
	29	Front Tread	1,470mm	1,470mm	1,600mm
	30	Rear Tread	1,700mm	1,700mm	1,700mm
	31	Front Tire	8.25-15-14	8.25-15-14	9.00-20-14
	32	Rear Tire	8.25-15-14	8.25-15.14	9.00-20-14